

RheoPac

PRODUCT DESCRIPTION

RheoPac is a dry powder fluid loss control additive designed for use in HDD drilling applications. When added to the drilling fluid, RheoPac reduces fluid loss to the formation and enhances the filter cake quality. Additionally, the regular version of RheoPac provides increased viscosity to the drilling fluid.

Not all Pac's are made the same. We do not use any fillers or cutting agents in our product, so you get the highest quality Pac with RheoPac.

RheoPac can be used as a stand-alone product, in conjunction with other additives, or with bentonite. It is compatible with other drilling chemicals.

RheoPac mixes easily into water, although good agitation is recommended to ensure proper mixing. Add 1/2 -2 canisters per 500 gallons of fluid through the mixing hopper.



PRODUCT ADVANTAGES

- Fluid Loss Control
- Provides thin, slick filter cake
- Provides bore hole stability
- Easy to mix and safe to use

PHYSICAL PROPERTIES

- Appearance: White powder
- Bulk Density: 35 – 40 lb/ft³
- Odor: Odorless
- pH: 6.0 – 8.0

PACKAGING

- Available in 1/2 gallon jugs, 5 gallon buckets.

GENERAL MIXING INSTRUCTIONS

12" HOLE & DOWN

Per 500 Gal

RheoPac For use with or without bentonite. Add 0.5 – 2 jugs as needed for fluid loss control.



DRILLCHEM.COM
281.713.8941

HOUSTON, TEXAS | LAFAYETTE, LOUISIANA | ELK CITY, OKLAHOMA
WILLISTON, NORTH DAKOTA | MIDLAND, TEXAS | CORPUS CHRISTI, TEXAS