

RheoXanD

PRODUCT DESCRIPTION

RheoXanD is a dry powder viscosifier designed for use in HDD drilling applications. When added to the drilling fluid, RheoXanD provides increased viscosity, enhancing cuttings suspension and removal.

RheoXanD can be used as a stand-alone product, in conjunction with other additives, or with bentonite. It is compatible with other drilling chemicals.

RheoXanD mixes easily into water, although good agitation is recommended to ensure proper mixing. Add 1/2 -2 canisters per 500 gallons of fluid through the mixing hopper.



PRODUCT ADVANTAGES

- Excellent Viscosifier
- Compatible with bentonite and other additives
- Enhances hole cleaning
- Easy to mix and safe to use

GENERAL MIXING INSTRUCTIONS

12" HOLE & DOWN

Per 500 Gal

RheoXanD For use with or without bentonite. Add 0.5 – 2 jugs until viscosity reaches desired level.

PHYSICAL PROPERTIES

- Appearance: Tan powder
- Bulk Density: 35 – 40 lb/ft³
- Odor: Sweet
- pH: 5.0 – 6.6

PACKAGING

- Available in 1/2 gallon jugs, 5 gallon buckets.



DRILLCHEM.COM
281.713.8941

HOUSTON, TEXAS | LAFAYETTE, LOUISIANA | ELK CITY, OKLAHOMA
WILLISTON, NORTH DAKOTA | MIDLAND, TEXAS | CORPUS CHRISTI, TEXAS