

COIL-LUBE GTE

PREMIUM POP LUBRICANT

PRODUCT DESCRIPTION

COIL-LUBE GTE is a highly concentrated blend of liquid lubricants designed for use during high friction environments in coiled tubing and workover operations. Composed of highly active film-forming lubricants and surfactants, COIL-LUBE GTE creates a lubricating layer between the work string and casing to significantly reduce drag.

Specifically designed for use in completion/workover fluids, COIL-LUBE GTE is compatible with high TDS water and other completion fluid chemicals.

Typical treatments range from 0.25 – 1.0 gals/ 10 bbls, and can be applied at 5 gal/ 10 bbls in slugs for extreme friction environments or to free stuck pipe. As always, pilot testing is recommended prior to field applications.

PRIMARY APPLICATIONS

- ✓ Highest potency pipe-on-pipe lubricant on the market.
- ✓ For use in high friction and stuck pipe situations.
- ✓ Compatible with high TDS water and other completion chemicals.
- ✓ Concentrated formula.
- ✓ Will not damage rubber components in down hole tools.
- ✓ Solids, temperature and contaminant resistant.

PHYSICAL PROPERTIES

- ✓ Appearance: Dark Redish /amber Liquid
- ✓ Bulk Density: 7.8 # / gal

PACKAGING

- ✓ COIL-LUBE GTE is packaged in 5 gallon pails and 330 gallon totes.



Houston, Midland, Stockdale, Texas | Enid, Oklahoma | Lafayette, Louisiana |
Minot, Williston, North Dakota | Casper, Wyoming

☎ 281-713-8941 | 🌐 DRILLCHEM.COM