

# COIL-LUBE XR

PROPRIETARY ENGINEERED POP LUBRICANT

## PRODUCT DESCRIPTION

COIL-LUBE XR is an engineered blend of synthetics and esters that have an affinity for metal-on-metal surfaces. COIL-LUBE XR was created to reduce the friction between the coiled tubing and the casing. An immediate effect can be seen when added to fluid systems at concentrations as low as 0.06% (1 quart per 10 barrels).

The anti-accretion qualities stop BHA balling while enhancing ROP and reducing differential sticking tendencies of tubulars, wireline tools, and coiled tubing.

## PRIMARY APPLICATIONS

- ✓ No emulsification.
- ✓ Will not cause foaming issues.
- ✓ Compatible in oil, synthetic and aqueous solutions.
- ✓ Non-toxic/non-flammable/non-combustible.
- ✓ Will not damage rubber components in MWD, LWD, or mud motors.
- ✓ Solids, temperature and contaminant resistant.
- ✓ 85% reduction in the coefficient of friction with a 1% concentration.
- ✓ Environmentally friendly, non-regulated.

## PHYSICAL PROPERTIES

- ✓ Appearance: Black Liquid
- ✓ Bulk Density: 7.8 # / gal

## PACKAGING

- ✓ COIL-LUBE XR is packaged in 5 gallon pails, and 330 gallon totes.



Houston, Midland, Stockdale, Texas | Enid, Oklahoma | Lafayette, Louisiana |  
Minot, Williston, North Dakota | Casper, Wyoming

☎ 281-713-8941 | 🌐 DRILLCHEM.COM