

DRILL-LUBE OBM

PRODUCT DESCRIPTION

DRILL-LUBE OBM is an engineered blend of lubricants and wetting agents designed for use in non-aqueous fluids where problems associated with torque, drag, and sliding exist.

Specifically designed for use in oil and synthetic based mud systems, DRILL-LUBE OBM is effective in a wide range of mud densities, and is tolerant to at least 350°F. It is compatible with base fluids and mud additives that may be present or added to the mud system.

Treatment levels range from 1.0 – 3.0% by volume in the mud system, while pills typically contain 1.0 – 5.0%, depending on the degree of problems encountered. As always, pilot testing is recommended prior to field applications.

PRIMARY APPLICATIONS

- ✓ Designed for use in oil and synthetic based mud systems
- ✓ Torque and drag reduction
- ✓ ROP enhancement
- ✓ Excellent thermal stability; stable up to 350°F

PHYSICAL PROPERTIES

- ✓ Appearance: Dark brown to black liquid
- ✓ pH: 6.5 – 8.5 (as aqueous solution)
- ✓ Pour Point: -20°F

PACKAGING

- ✓ DRILL-LUBE OBM comes in 55-gallon and 330-gallon poly totes



Houston, Midland, Stockdale, Texas | Enid, Oklahoma | Lafayette, Louisiana |
Minot, Williston, North Dakota | Casper, Wyoming

☎ 281-713-8941 | 🌐 DRILLCHEM.COM