

HEAVY-DUTY HDD

HYDROSLIDE

PRODUCT DESCRIPTION

HydroSlide is an environmentally friendly lubricant designed for use in HDD drilling applications. HydroSlide provides superior lubricity and prevents sticky clays from sticking to the rods and tooling.

HydroSlide has an affinity to metal surfaces and coats the rods and tooling, reducing torque and drag during drilling and pull back.

Can be used in conjunction with other additives, or with bentonite. It is compatible with other drilling chemicals.

Mixes easily into water, although good agitation is recommended to ensure proper mixing.

GENERAL MIXING INSTRUCTIONS

Per 1,000 Gal

To reduce torque and drag while drilling and pulling pipe: Add 10 - 30 gallons of HydroSlide per 1,000 gallons of drilling fluid.

The above mixing instructions are based on average dosages. Actual dosages in the field may vary based on soil and drilling conditions.



PRODUCT ADVANTAGES

- Hydrocarbon free
- Excellent lubricant
- Prevents clays from sticking to the rods and tooling
- Easy to mix and safe to use
- Environmentally friendly

PHYSICAL PROPERTIES

- Appearance: Amber liquid
- Odor: Bland
- Specific Gravity: 0.89 – 0.91
- Flash Point: >390°F

PACKAGING

- Available in 5 gallon buckets, 55 gal drum, and 330 gal totes.



DRILLCHEM.COM
281.713.8941

HOUSTON, TEXAS | LAFAYETTE, LOUISIANA | ELK CITY, OKLAHOMA
WILLISTON, NORTH DAKOTA | MIDLAND, TEXAS | CORPUS CHRISTI, TEXAS