

HEAVY-DUTY HDD

RheoXanD

PRODUCT DESCRIPTION

RheoXanD is a dry powder viscosifier designed for use in HDD drilling applications. When added to the drilling fluid, RheoXanD provides increased viscosity, enhancing cuttings suspension and removal.

RheoXanD can be used as a stand-alone product, in conjunction with other additives, or with bentonite. It is compatible with other drilling chemicals.

RheoXanD mixes easily into drilling fluid, although good agitation is recommended to ensure proper mixing.

GENERAL MIXING INSTRUCTIONS

Per 1,000 Gal

For increased viscosity of the drilling fluid, add 1 - 2 vis cups (2 lbs - 4 lbs) of RheoXanD per 1,000 gal of fluid. Add in 1 vis cup increments if additional viscosity is needed.

The above mixing instructions are based on average dosages. Actual dosages in the field may vary based on soil and drilling conditions.



PRODUCT ADVANTAGES

- Excellent viscosifier
- Compatible with bentonite and other additives
- Enhances hole cleaning
- Easy to mix and safe to use

PHYSICAL PROPERTIES

- Appearance: Tan powder
- Bulk Density: 35 – 40 lb/ft³
- Odor: Sweet
- pH: 5.0 – 6.6

PACKAGING

- Available in 25 lb bags, 25 kg bags, and 5 gallon buckets (round bucket); palletized and shrink wrapped.



DRILLCHEM.COM
281.713.8941

HOUSTON, TEXAS | LAFAYETTE, LOUISIANA | ELK CITY, OKLAHOMA
WILLISTON, NORTH DAKOTA | MIDLAND, TEXAS | CORPUS CHRISTI, TEXAS